



A3/A5 Series Pumps



UL Component Recognized

- Rated for use with steam condensate
- Fully automatic operation
- Available voltages:
 - A3 - 115, 208/230, 277
 - A5 - 115, 208/230, 380/460
- Discharge connections
 - A3 - 3/8 inch copper compression connection
 - A5 - 1/2 inch copper compression connection
- Heavy duty construction for commercial applications
- Reversible reservoir allows installation flexibility
- Built in check valve, easily disassembles for cleaning
- Quick disconnect discharge feature for easy servicing
- Motor bearings have double protection against water splash and steam vapor
- Auxiliary safety switch included on all models
- Stainless steel shaft for corrosion resistance
- Die cast aluminum impeller
- Heavy duty threaded impeller attachment
- 3 lead wires and conduit conversion standard
- Inlet and discharge rotate to reduce strain on tubing and piping
- Standard low level inlet barbed tubing connection (requires site modification)

12 Month Warranty

MODEL	PART NO.	hp @ rpm	MOTOR			Aux Switch	20' Tubing	Wt. (lbs)	Dimensions (in.)			Pump Performance Gals/Hour @ lift of						Shut off
			VAC	Amps					W	D	H	6'	12'	18'	24'	36'	48'	
A3		30 Foot Head – 1 Gal. Reservoir – Max. Temperature 212° F																
A3X-115	806029	1/10 @ 3450	115	3.1	Y	N	11	8.0	12.0	10.5	351	309	245	180	-	-	30'	
A3X-230	806028	1/10 @ 3450	208/230	1.1	Y	N	11	8.0	12.0	10.5	351	309	245	180	-	-	30'	
A3X-277	806030	1/10 @ 3450	277	1.0	Y	N	11	8.0	12.0	10.5	351	309	245	180	-	-	30'	
A5		60 Foot Head – 1 Gal. Reservoir – Max. Temperature 212° F																
A5X-115	806025	1/2 @ 3450	115	6.0	Y	N	15	8.0	12.0	10.5	550	528	495	462	390	306	60'	
A5X-230	806026	1/2 @ 3450	208-230	3.3	Y	N	15	8.0	12.0	10.5	550	528	495	462	390	306	60'	
A5X-460	806027	1/2 @ 3450	380-460	1.1	Y	N	15	8.0	12.0	10.5	550	528	495	462	390	306	60'	