

A2 Series Pumps

For applications where cast aluminum construction is required.



- 1 gallon cast aluminum reservoir
- Unitized construction
- Usable lifts to 22 feet
- Commercial application
- Snap action switch
- 6' cord and plug
- Stainless steel shaft
- Thermally protected motor

1 Year Warranty

MODEL	PART NO.	hp @ rpm	MOTOR			Aux Switch	20' Tubing	Wt. (lbs)	Dimensions (in.)			Pump Performance				Shut off
			VAC	Amps					W	D	H	Gals/Hour @ lift of	6'	12'	18'	
A2	22 Foot Head – 1 Gal. Reservoir – Max. Temperature 150° F											6'	12'	18'	20'	
A2-X115	851012	1/10 @ 3000	115	3.1	Y	N	12	6	9	10	185	139	79	51	22'	
A2-X230	851017	1/10 @ 3000	230	1.5	Y	N	12	6	9	10	185	139	79	51	22'	

A2-SA Series Pumps

The A2-SA series is designed for heavy duty removal of high temperature condensate.



- 1 gallon heavy duty aluminum reservoir
- Snap action switch, adjusted at factory
- 1/10 hp 3,000 rpm motor with stainless steel shaft
- Inlet; 1-3/8" ID; Outlet; 3/8" INPT
- 6 foot cord and plug on A2-SA
- 3 lead wires on A2-SA-UR
- Heavy duty design for individual applications
- Allows condensate removal without having floor drains

1 Year Warranty

MODEL	PART NO.	hp @ rpm	MOTOR			Aux Switch	20' Tubing	Wt. (lbs)	Dimensions (in.)			Pump Performance				Shut off
			VAC	Amps					W	D	H	Gals/Hour @ lift of	6'	12'	18'	
A2-SA	19.5 Foot Head – 1 Gal. Reservoir – Max. Temperature 212° F											6'	12'	18'	20'	
A2-SA-X115	851124	1/10 @ 3000	115	3.5	Y	N	12	6	9	11	185	139	79	51	22'	
A2-SA-X230	851125	1/10 @ 3000	230	2.0	Y	N	12	6	9	11	185	139	79	51	22'	
A2-SA-UR230	851034	1/10 @ 3000	230	2.0	N	N	12	6	9	11	185	139	79	51	22'	