



A2 Series Pumps

For applications involving high surges of water. Particularly suited for commercial ice machines and the high volumes of water produced during the cleaning flush cycles.



- 2 gallon cast aluminum reservoir
- All other features identical to model A pumps
- Snap action switch
- 6 ft cord and plug
- Stainless steel shaft
- Thermally protected motor

1 Year Warranty

MODEL	PART NO.	hp @ rpm	MOTOR		Aux Switch	20' Tubing	Wt. (lbs)	Dimensions (in.)			Pump Performance Gals/Hour @ lift of				Shut off
			VAC	Amps				W	D	H	6'	12'	18'	20'	
AL2		22 Foot Head – 2 Gal. Reservoir – Max. Temperature 150° F													
AL2-X115	851030	1/10 @ 3000	115	3.1	Y	N	17	12	9	10	185	139	79	51	22'
AL2-X230	851032	1/10 @ 3000	230	1.5	Y	N	17	12	9	10	185	139	79	51	22'

A2X-1965 Series Pumps



- Dual voltage, thermally protected motor
- Choice of three 1-1/4" top inlets or 3/4" FNPT at bottom of reservoir
- Includes auxiliary safety switch
- Generally accepted for use in "Plenum Rated" applications
- Junction box wire connections, with 3/4" knock out for conduit

MODEL	PART NO.	hp @ rpm	MOTOR		Aux Switch	20' Tubing	Wt. (lbs)	Dimensions (in.)			Pump Performance Gals/Hour @ lift of				Shut off
			VAC	Amps				W	D	H	6'	12'	18'	20'	
A2		22 Foot Head – 1 Gal. Reservoir – Max. Temperature 150° F													
A2X-1965*	851117	1/10 @ 3000	115/230	3.5/1.7	Y	N	10	6	9	10	185	139	79	51	22'

*Replaces KESCO 1965