

Alarms for Sump, Sewage and Effluent



ALM-2 (20' float cord) ALM-2-1 (10' float cord)

- Nema 1 Indoor rated
- 115V operation with 9 volt battery back-up
- 86 decible horn
- Red alarm light
- Green "power-on" light
- Low battery chirp
- Automatic reset
- Test / Silence feature



ALM-P1 Alarm with Probe Sensor

- Indoor alarm
- 115 Volt
- 9V battery back-up
- Compact probe mounted sensor (snaps on 1-1/4" or 1-1/2" discharge pipe)
- Auxiliary contacts
- Visual and audio alarm



ALM-2W Outdoor

- Meets Type 3R water-tight standards
- 115V operation
- Thermoplastic enclosure
- Red alarm beacon, 360° visible
- 85 decible horn
- Test / Silence switch
- 20' Float cord



ADC-1 Auto Dialer for Alarms and Control Panels

On vacation or away from home?

Get notification of an alarm condition dialed directly to your phone!

- Can sequentially dial up to 4 telephone numbers
- Delivers up to a 16 second message you can record
- 9-12 volt DC operation
- Mounts flat on wall
- Ability to program a pause and pound (#) tone into dialing sequence
- For indoor mounting only
- LED display

NOTE: this unit requires auxiliary contacts on the source alarm or control panel

Call your cell phone

Call your plumbing contractor

Call your family

Call your neighbor



ALM-3W Commercial Outdoor

- Nema 4X rated
- Commercial-duty enclosure
- 115V operation. Direct wire.
- Red alarm beacon, 360° visible
- 88 decible horn
- Alarm "Test / On / Silence" switch
- 20' float cord
- Includes auxiliary contacts