



Visit our website: www.bjmpumps.com

4/19/2010
0802
Supersedes
0801

TECHNICAL DATA
MODEL LWA15
LIGHT WEIGHT AGITATOR DEWATERING PUMP—CHROME IRON / DUCTILE IRON

GENERAL DATA

MAX. FLOW: GPM (L/min)	181 GPM (685 L/min)
MAX. HEAD: ft (m)	55' (17 m)
PUMP TYPE	TOP DISCHARGE, DEWATERING, AGITATOR
SOLID SIZE: in (mm)	0.4" (11 mm)
MAX. SUBMERSION DEPTH: ft (m)	65' (20m) or limited to length of power cord, Consult factory for deeper depths
MIN. SUBMERSION DEPTH: ft (m)	7.6" (194 mm)
DISCHARGE SIZE	3" NPT
PUMP WEIGHT, without cable: lbs (kg)	93 lbs. (42 kg)
SHIP WEIGHT: lbs (kg)	128 lbs. (58 kg)

CONSTRUCTION / MATERIAL DATA

MECHANICAL SEAL - UPPER	CARBON/CERAMIC
MECHANICAL SEAL - LOWER	SILICON CARBIDE/SILICON CARBIDE
MOTOR HOUSING	304 SS
PUMP VOLUTE	HARDENED DUCTILE IRON, 223 BHN
SUCTION COVER	HARDENED DUCTILE IRON, 477BHN
AGITATOR	HARDENED DUCTILE IRON, 477 BHN
IMPELLER	HIGH CHROME, 653 BHN
STRAINER/STAND	STEEL
LIP SEALS & O-RINGS	BUNA-N
ROTOR SHAFT	304 SS
EXTERNAL HARDWARE	304 SS

ELECTRICAL / MOTOR DATA

MOTOR: TYPE, RATING HP	SUBMERSIBLE, 2 (CONTINUOUS DUTY)		
MOTOR RPM	3450		
MOTOR INSULATION CLASS	F		
MOTOR SERVICE FACTOR	1.15		
VOLTAGE - 3 PH, 60 Hz	230V	460V	575V
CURRENT F.L.A.	5.8	2.9	2.3
MOTOR PROTECTION	AUTO RE-SET AMP OVERLOAD SWITCH		
POWER CORD: GAGE; LENGTH; TYPE	A.W.G. 14/5; 50' (15 m); SOOW(EPR JACKET)		
MAXIMUM LIQUID TEMPERATURE	104°F (40°C)		

©2010 BJM Pumps, LLC. All rights reserved.

123 Spencer Plain Road
Old Saybrook, CT. 06475, USA
(860)399-5937 - (877) BJM-PUMP - Fax: (860)399-7784
REFER TO REVERSE SIDE FOR PUMP PERFORMANCE CURVES
SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE



MODEL: LWA15

