



rotech
PUMPS & SYSTEMS INC.

"Your Source to Fluid handling"

SPT Series Pumps Model SPT 8

Self-Priming

650 rpm (2.7m) 9ft - 750 rpm 3.7 (12ft)
 850 rpm (4.6m) 15ft - 950 rpm 5.2m (17ft)
 1050 rpm (6.1m) 20ft - 1150 rpm 6.4m (21ft)
 1250 rpm (6.7m) 22ft - 1350 rpm 7.0m (23ft)

Technical Data

Impeller Dia. 374.65 mm (14.3/4")
 R.P.M. from 650 rpm to 1350 rpm
 Max. Solids 76.2 mm (3")
 Net Weight 581kg (1295 lbs)
 Shipping Weights 634kg (1399 lbs)

* Before using this table, check the NPSH.

are designed for economical & trouble-free operation in handling solids-laden liquids and slurries. Pumps feature a large volute design which allows them to re-prime automatically in a completely open system without the need of suction or discharge check valves. And this is workable with the pump only partially filled with liquid and completely dry suction line. Pumps will be able to handle up to 75mm spherical solids, depending on pump models. In case that pump shaft or bearings need service or repair, the entire rotating assembly can be removed without disturbing pump casing or pipelines. Rotating assembly is sealed with an O-Ring, allowing for external adjustments of clearance.

Performance Curve (8" x 8")



