



rotech
PUMPS & SYSTEMS INC.

"Your Source to Fluid handling"

SPU Series Pumps Model SPU 4

Self-Priming

850 rpm (2.4m) 8ft - 1150 rpm 3.0m (10ft)
 1450 rpm (3.6m) 12ft - 1750 rpm 3.9m (13ft)
 1950 rpm (4.5m) 15ft - 2150 rpm 5.2m (17ft)

Technical Data

Impeller Dia.	279.4mm (11")
R.P.M.	from 850 rpm to 2150 rpm
Max. Solids	28.57 mm (1.1/8")
Net Weight	272kg (600 lbs)
Shipping Weights	297kg (655 lbs)

* Before using this table, check the NPSH.

are designed for economical & trouble-free operation in handling solids-laden liquids and slurries. Pumps feature a large volute design which allows them to re-prime automatically in a completely open system without the need of suction or discharge check valves. And this is workable with the pump only partially filled with liquid and completely dry suction line. Pumps will be able to handle up to 75mm spherical solids, depending on pump models. In case that pump shaft or bearings need service or repair, the entire rotating assembly can be removed without disturbing pump casing or pipelines. Rotating assembly is sealed with an O-Ring, allowing for external adjustments of clearance.

Performance Curve (4" x 4")



